Amazzonia

TECHNICAL DATA

DECO-TILE

AMAZZONIA

TECHNICAL FEATURES

	standards	test results*
product classification	UNI EN 14411-G ISO 13006	group Bla fully vitrified
dimensional and surface quality	UNI EN ISO 10545-2	very low tolerance
water absorption	UNI EN ISO 10545-3	< 0,1%
flexural strength	UNI EN ISO 10545-4	45 N/mm^2
frost resistance	all standards	guaranteed
resistance to acids and alkalis (with the exception of hydrofluoric acid)	UNI EN ISO 10545-13	A
wear and abrasion resistance	UNI EN ISO 10545-6	≤ 150 mm^3
linear thermal expansion	UNI EN ISO 10545-8	6 x 10^{-6}
stain resistance	UNI EN ISO 10545-14	4 - 5 guaranteed
slip resistance (Matt surface)	DIN EN 16165 ANNEX B - ANNEX A	Matt **R10 A** Grip **R11 A+B+C**
	D.M. N° 236 DEL 14.06.89 METODO B.C.R.	valore μ > 0,40
	DIN EN 16165 ANNEX C	PTV > 36***
colour resistance to sunlight exposure	DIN 51094	no change of colours

* approx value
*** test on a dry surface

Just like the natural materials they are inspired by, the aesthetics, colouration and veining of the tiles can differ.



For 120 cm (48") and 60 cm (24") long tiles, staggering should not exceed 20 cm (8").

DECO-TILE

DECO-TILE

STAY CONNECTED
-
www.decotile.com
@decotile

Locations

Toronto
Head Office + Warehouse

143 Tycos Dr.
Toronto, ON M6B 1W6
416 413 7985

Oakville
Showroom

550 Speers Rd. Unit #2
Oakville, ON L6K 2G3
905 582 7985