Marmoker

TECHNICAL DATA

DECO-TILE

TECHNICAL FEATURES

	standards	test results*
product classification	UNI EN 14411-G ISO 13006	group Bla fully vitrified
dimensional and surface quality	UNI EN ISO 10545-2	very low tolerance
water absorption	UNI EN ISO 10545-3	< 0,1%
flexural strength	UNI EN ISO 10545-4	45 N/mm^2
frost resistance	all standards	guaranteed
resistance to acids and alkalis (with the exception of hydrofluoric acid)	UNI EN ISO 10545-13	A
wear and abrasion resistance	UNI EN ISO 10545-6	≤ 150 mm^3
linear thermal expansion	UNI EN ISO 10545-8	6 x 10^{-6}
stain resistance	UNI EN ISO 10545-14	4 - 5 guaranteed
slip resistance (Matt surface)	DIN EN 16165 ANNEX B / ANNEX A	Honed **R9** Naturale **R10 A+B PTV>36**
	D.M. N° 236 DEL 14.06.89 METODO B.C.R.	valore μ > 0,40
	DIN EN 16165 ANNEX C	PTV > 36***
colour resistance to sunlight exposure	DIN 51094	no change of colours

* approx value

*** test on a dry surface

Just like the natural materials they are inspired by, the aesthetics, colouration and veining of the tiles can differ.

DECO-TILE

DECO-TILE

STAY CONNECTED
-
www.decotile.com
@decotile

Locations

Toronto
Head Office + Warehouse

143 Tycos Dr.
Toronto, ON M6B 1W6
416 413 7985

Oakville
Showroom

550 Speers Rd. Unit #2
Oakville, ON L6K 2G3
905 582 7985