Trend Vitreo

TECHNICAL DATA

DECO-TILE

VITREO
WEIGHT AND DIMENSIONS | 2 x 2 cm | 3/4" x 3/4"

SIZE	2 x 2 cm | 3/4" x 3/4"
THICKNESS	~ 4 mm | 5/32"
SHEETS SIZE	31,6 x 31,6 cm 12 7/16" x 12 7/16"
JOINT	~ 1 mm | 2/48"
WEIGHT	~7 kg/m² | 1.6 lbs/SQF
QUANTITY PER CARTON	2 m² | 21.528 SQF
CARTONS PER PALLET	72
PALLET WEIGHT	~ 1030 Kg | ~ 2266 lb

TEST ASTM

TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS
Range of thickness (ASTM C499)	passes
Facial dimensions (ASTM C499)	passes
Wedging (ASTM C502)	passes
Water absorption (ASTM C373)	passes
Thermal shocks (ASTM C484)	passes
Bond Strenght (ASTM C482)	passes

TEST DATA

UNI EN ISO 10545 (13)

RESISTANCE TO CHEMICAL AGENTS	resistant

UNI EN ISO 10545 (9)

RESISTANCE TO THERMAL SHOCKS	resistant

UNI EN ISO 10545 (3)

WATER ABSORPTION	none

DIN 51094

COLOURS RESISTANCE TO FADING	resistant

UNI EN ISO 10545 (12)

FROST RESISTANCE	resistant

DIN 51097

SLIP RESISTANCE ON BARE FEET	class C

DIN 51130

SLIP RESISTANCE WITH SHOES	R9

SPECIFICATIONS

VITREO
Fused semi-transparent coloured glass mosaic, formed with 1 x 1 cm and 2 x 2 cm square tiles, with a thickness of about 4 mm, bevelled, with a size of 31.6 x31.6 cm with an approximately 1 mm joint. Composite with up to a maximum of 45% quality materials, pre-consumer recycled glass, and up to a maximum of 55% of post-consumer recycled glass.

VITREO GRIP
SPECIAL PROCESSING

VITREOGRIP		
GRIP		
COLOURS | COLORI | COULEURS | FARBEN | COLORES | ЦВЕТЫ: 101 | 104 | 105 | 107 | 109 | 110 | 111 | 113 | 115 | 116 | 117 | 119 | 120 | 121 | 122 | 123 | 130 | 131 | 132 | 135 | 136 | 137 | 138 | 140 | 142 | 150 | 152 | 153 | 154 | 155 | 160 | 161 | 163 | 165 | 166 | 167 | 169 | 170 | 171 | 172 | 173 | 180 | 181 | 182 | 183		
DIN 51097		
SLIP RESISTANCE ON BARE FEET	class	C
DIN 51130		
SLIP RESISTANCE WITH SHOES		R11

DECO-TILE

STAY CONNECTED
-
www.decotile.com
@decotile

Locations

Toronto
Head Office + Warehouse

143 Tycos Dr.
Toronto, ON M6B 1W6
416 413 7985

Oakville
Showroom

550 Speers Rd. Unit #2
Oakville, ON L6K 2G3
905 582 7985